



# Innovative Tex

High Tech fiber & Metal wires  
Hybrid Fabrics

## TEXTILE DATA SHEET

**G. Angeloni**  
REFERENCE

### GGCu 300 T - Blue

<b>CHARACTERISTICS</b>		<b>Nominal</b>	<b>Tolerance</b>	<b>Normative</b>
<b>Mass per unit area</b>	g/m <sup>2</sup>	300	± 5%	ISO 4605
<b>Weave</b>		<b>2x2 Twill</b>		ISO 2113
<b>Width</b>	mm	1000/1200	± 2,5%	ISO 22198
<b>Thickness</b>	mm	0,305	± 2,5%	ISO 5084(**)
<b>Other informations</b>		<i>Loomstate</i>		

  

<b>Nominal Construction</b>		<b>WARP</b>		<b>WEFT</b>	
<b>Fiber Description</b>		HR Carbon Fiber Grafil TR30 - S - 3K 200 tex		Textile Blue colored wire CU/Ag5 wire - 0,15 Grafil TR30 - S - 3K 200 tex	
<b>Fiber Producer</b>		Mitsubishi Grafil		Mitsubishi Grafil	
<b>Thread Count</b>	ends/cm	<b>7,00</b>	ISO 4602	<b>9,00</b>	ISO 4602
<b>Weight Distribution</b>	g/m <sup>2</sup>	Grafil TR30 - S -	140	CU/Ag5 wire -	96
	%	3K 200 tex	100%	0,15	62%
	g/m <sup>2</sup>			Grafil TR30 - S -	60
	%			3K 200 tex	38%
<b>Weight Rate</b>	%	47%		53%	
<b>Selvages</b>		Weaving style	LENO	Type of Fiber	HM polyester 22 tex

  

<b>Mechanical Properties of Fiber</b>	<b>Strength ( nominal )</b>	<b>Modulus ( nominal )</b>
Mitsubishi Grafil TR30-S 200 tex	3530 Mpa	230 GPa

(\*\*) Theoretical thickness for an epoxy laminate with 40% of reinforcement in volume.

Date of Issue	05/10/2016	No. of Pages	1
---------------	------------	--------------	---

Note : Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

**G. Angeloni srl**

via Abate Tommaso , 72/A5 - 30020 Quarto d'Altino (VE) - ITALY

Tel. +39 0422 823801 - 780580 Fax +39 0422 782782

E-Mail : info@g-angeloni.com